



**PROALL®**  
A TEREX BRAND

**L60**

the next generation  
of mobile concrete mixers

FOR MORE DETAILS  
+1 855.335.9500



## L60 MODEL

The L80 is lightweight aluminum mixer that provides accurate on-site concrete production and increased versatility.

## ADDITIONAL OPTIONS

### Body

- Aggregate Bin Liner
- 360° Swivel Chute
- Aluminum Tool Box
- Aerator System for Cement Bin
- Larger Cement Bin
- Pneumatic Fill
- Dual Water Tank Fill
- Fly Ash Bin

### Safety

- Standard System Rear Ladder & Platform
- Cement Bin Safety Rail

### Verification

- Belt Materials Sensors
- Gate Height
- Verification Sensors
- Load Cell System

### Application

- Additional Vibrators
- Color Feeder
- Fiber Feeder
- Guniting Auger
- Heat Exchanger
- Additional Admix Tanks

### Additional

- Pressure Washer
- Custom Paint
- Extra Oil Cooler
- Auto-Lube System
- PTO and Installation of PTO

## HIGHLIGHTED SPECIFICATIONS

Production Capacity	5.4m <sup>3</sup> / 7yd <sup>3</sup>
Production Rate	50m <sup>3</sup> /hr (65yd <sup>3</sup> /hr)
Aggregate Bin	4.5m <sup>3</sup> / 160ft <sup>3</sup>
Sand Bin	4.0m <sup>3</sup> / 143ft <sup>3</sup>
Cement Bin	2.1m <sup>3</sup> / 75ft <sup>3</sup>
Water Tank	1400L / 370gal

## STANDARD FEATURES

Wireless Remote	Variable Speed Cement Metering
Automated Admix System	Automated Chain Oil
Batch Ticketing System	Aluminum Fenders
Electronic Tarp System	Automated Electric Vibrators
Automated Water System	



Discover more about our options and how they can improve your businesses needs.

## OUR ADVANTAGE



Accuracy

Our Commander automated control system ensures accurate and consistent concrete production.



Operator Design

Commander prioritizes operator ease, offering a user-friendly interface and intuitive controls for seamless operation.



Customer Support

ProAll offers reliable customer support, providing prompt assistance for any inquiries or technical issues.

**GET IN TOUCH**



Sales: 1.855.335.9500  
Parts: 1.855.335.9500  
Support: 1.833.577.6255



Sales: ProAll.Info@Terex.com  
Parts: ProAll.Parts@Terex.com  
Support: ProAll.Support@Terex.com



Visit: [www.Proallinc.com](http://www.Proallinc.com)



## L60 MODEL

The L60 is lightweight aluminum mixer that provides accurate on-site concrete production and increased versatility.

### Standard Features

Model	L60
Product Capacity	5.4m <sup>3</sup> / 7yd <sup>3</sup>
Production Rate	50m <sup>3</sup> /hr (65yd <sup>3</sup> / hr)
Cement Bin	2.1m <sup>3</sup> / 75ft <sup>3</sup>
Water Tank	1400 L / 370 US gal
Aggregate Bin A	4.5m <sup>3</sup> / 160ft <sup>3</sup>
Aggregates Bin B	4.0m <sup>3</sup> / 143ft <sup>3</sup>
Admix Tank 1	40L / 10 gal
Admix Tank 2	80L / 20 gal
Mixing Auger Diameter/Length	(228mm) 9" / (2438mm) 96"
Operator Control	Console/ Wireless
Control System	Commander
Drive	By truck PTO
Two Way Remote	On-board remote
Tarp Cover	Mesh
Delivery Printer	On-board printer
L60 Unit Length	6579mm / 259"
L60 Unit Height	2477mm / 97.5"
L60 Unit Working Swing	120 degree
L60 Unit Weight (dry weight)	*3403 kg / 7503 lbs
Chain Lubrication	Automated
Water System	Automated
Vibrators	Electric
Hydraulic Pumps	High Efficiency Piston Pumps

\* depending on mounting configuration

