



**PROALL®**  
A TEREX BRAND

# L8025

the next generation of  
mobile concrete mixers

FOR MORE DETAILS  
**+1 855.335.9500**

## L8025 MODEL

The L8025 is a versatile and efficient concrete mixing machine that allows for on-site production, precise material measurements, and customizable batch sizes.



Commander 2.0 Control System  
\*Available on P-Models Only.



**COMMANDER®**

## HIGHLIGHTED SPECIFICATIONS

|                     |                                              |
|---------------------|----------------------------------------------|
| Production Capacity | 7.6m <sup>3</sup> / 10yd <sup>3</sup>        |
| Production Rate     | 50m <sup>3</sup> /hr (65yd <sup>3</sup> /hr) |
| Aggregate Bin       | 4.4m <sup>3</sup> / 156ft <sup>3</sup>       |
| Sand Bin            | 5.7m <sup>3</sup> / 200ft <sup>3</sup>       |
| Cement Bin          | 2.6m <sup>3</sup> / 93ft <sup>3</sup>        |
| Water Tank          | 2250L / 600gal                               |

## STANDARD FEATURES

|                        |                               |
|------------------------|-------------------------------|
| Wireless Remote        | System Variable Speed Cement  |
| Automated Admix        | Metering                      |
| System Batch Ticketing | Automated Chain Oil           |
| System Electric Tarp   | Automated Electric Vibrators  |
| System Automated Water | Aerator System for Cement Bin |
|                        | Aggregates Bin Extensions     |

## ADDITIONAL OPTIONS

### Body

- ☐ Aggregate Bin Liner
- ☐ 360° Swivel Chute
- ☐ Aluminum Tool Box
- ☐ Dual Water Tank Fill

### Safety

- ☐ Standard System Rear Ladder & Platform

### Verification

- ☐ Belt Materials Sensors
- ☐ Gate Height
- ☐ Verification Sensors

### Application

- ☐ Additional Vibrators
- ☐ Color Feeder
- ☐ Fiber Feeder
- ☐ Heat Exchanger
- ☐ Additional Admix Tanks

### Additional

- ☐ Pressure Washer
- ☐ Custom Paint
- ☐ Extra Oil Cooler
- ☐ Auto-Lube System



Discover more about our options  
and how they can improve your  
business's needs.

## OUR ADVANTAGE



### Accuracy

Our Commander automated control system ensures accurate and consistent concrete production.



### Operator Design

Commander prioritizes operator ease, offering a user-friendly interface and intuitive controls for seamless operation.



### Customer Support

ProAll offers reliable customer support, providing prompt assistance for any inquiries or technical issues.

**GET IN  
TOUCH**



Sales: 1.855.335.9500  
Parts: 1.855.335.9500  
Support: 1.833.577.6255



Sales: Proall.Info@Terex.com  
Parts: Proall.Parts@Terex.com  
Support: Proall.Support@Terex.com



[www.proallinc.com](http://www.proallinc.com)



## L8025 MODEL

The L8025 is a versatile and efficient concrete mixing machine that allows for on-site production, precise material measurements, and customizable batch sizes.

### Standard Features

|                              |                                                |
|------------------------------|------------------------------------------------|
| Model                        | L8025                                          |
| Product Capacity             | 7.6m <sup>3</sup> / 10yd <sup>3</sup>          |
| Production Rate              | 50m <sup>3</sup> / hr (65yd <sup>3</sup> / hr) |
| Cement Bin                   | 2.6/3.1m <sup>3</sup> / 93/110ft <sup>3</sup>  |
| Water Tank                   | 2250 L / 600 US gal                            |
| Aggregate Bin A              | 4.4m <sup>3</sup> / 156ft <sup>3</sup>         |
| Aggregate Bin B              | 5.7m <sup>3</sup> / 200ft <sup>3</sup>         |
| Admix Tank 1                 | 40L / 10 gal                                   |
| Admix Tank 2                 | 80L / 20 gal                                   |
| Mixing Auger Diameter/Length | (228mm) 9" / (2438mm) 96"                      |
| Operator Control             | Console/ Wireless                              |
| Control System               | Commander 2.0                                  |
| Drive                        | By truck PTO                                   |
| Two Way Remote               | On-board remote                                |
| Tarp Cover                   | Mesh                                           |
| Delivery Printer             | On-board printer                               |
| P95 Unit Length              | 6960mm / 274"                                  |
| P95 Unit Height              | 2477mm / 97.5"                                 |
| P95 Unit Working Swing       | 120 degree                                     |
| P95 Unit Weight (dry weight) | *3575 kg / 7881 lbs                            |
| Chain Lubrication            | Automated                                      |
| Water System                 | Automated                                      |
| Vibrators                    | Electric                                       |
| Hydraulic Pumps              | High Efficiency Piston Pumps                   |

\* depending on mounting configuration

