

L8025

the next generation of
mobile concrete mixers

FOR MORE DETAILS
+44 (0) 1625 856685



Commander 2.0 Control System
*Available on P-Models Only.


COMMANDER®

L8025 MODEL

The L8025 is a versatile and efficient concrete mixing machine that allows for on-site production, precise material measurements, and customizable batch sizes.

ADDITIONAL OPTIONS

Body

- ☐ Aggregate Bin Liner
- ☐ 360° Swivel Chute
- ☐ Aluminum Tool Box
- ☐ Dual Water Tank Fill

Safety

- ☐ Standard System Rear Ladder & Platform

Verification

- ☐ Belt Materials Sensors
- ☐ Gate Height
- ☐ Verification Sensors

Application

- ☐ Additional Vibrators
- ☐ Color Feeder
- ☐ Fiber Feeder
- ☐ Heat Exchanger
- ☐ Additional Admix Tanks

Additional

- ☐ Pressure Washer
- ☐ Custom Paint
- ☐ Extra Oil Cooler
- ☐ Auto-Lube System

HIGHLIGHTED SPECIFICATIONS

Production Capacity	7.6m ³ / 10yd ³
Production Rate	50m ³ /hr (65yd ³ /hr)
Aggregate Bin	4.4m ³ / 156ft ³
Sand Bin	5.7m ³ / 200ft ³
Cement Bin	2.6m ³ / 93ft ³
Water Tank	2250L / 600gal

STANDARD FEATURES

Wireless Remote	System Variable Speed Cement
Automated Admix	Metering
System Batch Ticketing	Automated Chain Oil
System Electric Tarp	Automated Electric Vibrators
System Automated Water	Aerator System for Cement Bin
	Aggregates Bin Extensions



Discover more about our options
and how they can improve your
business's needs.

OUR ADVANTAGE



Accuracy

Our Commander automated control system ensures accurate and consistent concrete production.



Operator Design

Commander prioritizes operator ease, offering a user-friendly interface and intuitive controls for seamless operation.



Customer Support

ProAll offers reliable customer support, providing prompt assistance for any inquiries or technical issues.

**GET IN
TOUCH
ARMCON®**

Official UK ProAll Dealership



+44 (0) 1625 856685



Sales: Proall.Info@Terex.com
Parts: Proall.Parts@Terex.com
Support: Proall.Support@Terex.com



www.proallinc.com



L8025 MODEL

The L8025 is a versatile and efficient concrete mixing machine that allows for on-site production, precise material measurements, and customizable batch sizes.

Standard Features

Model	L8025
Product Capacity	7.6m ³ / 10yd ³
Production Rate	50m ³ /hr (65yd ³ /hr)
Cement Bin	2.6/3.1m ³ / 93/110ft ³
Water Tank	2250 L / 600 US gal
Aggregate Bin A	4.4m ³ / 156ft ³
Aggregate Bin B	5.7m ³ / 200ft ³
Admix Tank 1	40L / 10 gal
Admix Tank 2	80L / 20 gal
Mixing Auger Diameter/Length	(228mm) 9" / (2438mm) 96"
Operator Control	Console/ Wireless
Control System	Commander 2.0
Drive	By truck PTO
Two Way Remote	On-board remote
Tarp Cover	Mesh
Delivery Printer	On-board printer
P95 Unit Length	6960mm / 274"
P95 Unit Height	2477mm / 97.5"
P95 Unit Working Swing	120 degree
P95 Unit Weight (dry weight)	*3575 kg / 7881 lbs
Chain Lubrication	Automated
Water System	Automated
Vibrators	Electric
Hydraulic Pumps	High Efficiency Piston Pumps

* depending on mounting configuration

