

L20R

the next generation
of mobile concrete mixers

FOR MORE DETAILS ———
+1 855.335.9500



L20R MODEL

The L20R is a lightweight, versatile and efficient volumetric concrete mixer that delivers just what you need, when you need it.

HIGHLIGHTED SPECIFICATIONS

Production Capacity	Up to 2m ³ / 2.6yd ³
Hourly Production Rate	Up to 15m ³ /20yd ³
Cement Bin	0.6m ³ / 20ft ³
Water Tank	380L / 100gal
Aggregate Bin A	1.2m ³ / 42ft ³
Aggregate Bin B	1.1m ³ / 39ft ³

STANDARD FEATURES

On board batch system with mix design and job storage	Vibrators: Aggregate bins, cement bin, cement bag loader
Automated Water System (Operator controlled)	Tarp: Mesh manual open/close
High Efficiency Hydraulic Pump	Auger: 8" AR fl
Side ladder	ighting, Repairable 360°
Fixed Cement Metering	Swivel Chute
Automatic Chain Oil	



ADDITIONAL OPTIONS

Three liquid admixture dosing system. 2x 40L, 1 x80L (2x 10.5gal, 1x 21gal)



Discover more about our options and how they can improve your businesses needs.

OUR **ADVANTAGE**



Accuracy

Our Commander automated control system ensures accurate and consistent concrete production.



Operator Design

Commander prioritizes operator ease, offering a user-friendly interface and intuitive controls for seamless operation.



Customer Support

ProAll offers reliable customer support, providing prompt assistance for any inquiries or technical issues.

**GET IN
TOUCH**



Sales: 1.855.335.9500
Parts: 1.855.335.9500
Support: 1.833.577.6255



Sales: Proall.Info@Terex.com
Parts: Proall.Parts@Terex.com
Support: Proall.Support@Terex.com



Visit: www.Proallinc.com



L20R MODEL

The L20R is a lightweight, versatile and efficient volumetric concrete mixer that delivers just what you need, when you need it.

Standard Features

Model	L20R
Control Console/Wireless System	Ranger control with integrated mix calculator and mix design storage. Electric operated, manual controls.
Delivery Printer	No
Two Way Remote	No
Drive	Truck PTO
Tarp Cover	Mesh manual open / close
Unit Length	Depends on Chassis
Unit Height	Depends on Chassis
Unit Working Swing	N/A no swing
Unit Weight (dry weight)	Under 25,950 lbs GVWR (with right chassis)
Mixing Auger Diameter/Length	8" AR flight, 84", repairable
Chain Lubrication	Yes
Water System	100 gallon standard
Vibrators	Electric (Aggregate bins, cement bin, cement bag loader)
Hydraulic Pumps	Rexroth
Cement Bin capacity options	No
Admix Tank 1 capacity	40L (if optional admix selected)
Admix Tank 2 capacity	40L (if optional admix selected)
Cement bag fill system	Standard
Non-CDL operation	Non-CDL to operate (or local license for weight)
Basic controls	Knobs to match target indicated
Simple calibration	Supported for basic mix designs and up to three admixtures
Skid steer loadable	Yes - 100" rail side for loading
Cement bag loading	Yes - silo not needed
Operator training alignment	All screen pages follow same layout as PROALL COMMANDER series
Chassis options	Ford F650, International MV-607, Freightliner M2-106 (ProAll supplied) or customer supplied (minimum 23,000 lbs)
Voltage	12VDC
Powder coat color	White (standard)

