

L20R

the next generation
of mobile concrete mixers

FOR MORE DETAILS

+1 855.335.9500



L20R MODEL

The L20R is a lightweight, versatile and efficient volumetric concrete mixer that delivers just what you need, when you need it.

HIGHLIGHTED SPECIFICATIONS

Production Capacity	2m ³ / 2.6yd ³
Hourly Production Rate	15m ³ / 20yd ³
Cement Bin	0.6m ³ / 20ft ³
Water Tank	380L / 100gal
Aggregate Bin A	1.2m ³ / 42ft ³
Aggregate Bin B	1.1m ³ / 39ft ³

STANDARD FEATURES

On board batch system with mix design and job storage	Vibrators: Aggregate bins, cement bin, cement bag loader
Automated Water System (Operator controlled)	Tarp: Mesh manual open/close
High Efficiency Hydraulic Pump	Auger: 8" / 203 mm AR flighting,
Side ladder	Repairable 360° Swivel Chute
Fixed Cement Metering	
Automatic Chain Oil	
Aluminum Fenders	



ADDITIONAL OPTIONS

Three liquid admixture dosing system. 2x 40L, 1 x80L (2x 10.5gal, 1x 21gal)



Discover more about our options and how they can improve your businesses needs.

OUR **ADVANTAGE**



Accuracy

Our Commander automated control system ensures accurate and consistent concrete production.



Operator Design

Commander prioritizes operator ease, offering a user-friendly interface and intuitive controls for seamless operation.



Customer Support

ProAll offers reliable customer support, providing prompt assistance for any inquiries or technical issues.

GET IN TOUCH



Sales: 1.855.335.9500
Parts: 1.855.335.9500
Support: 1.833.577.6255



Sales: Proall.Info@Terex.com
Parts: Proall.Parts@Terex.com
Support: Proall.Support@Terex.com



Visit: www.Proallinc.com



L20R MODEL

The L20R is a lightweight, versatile and efficient volumetric concrete mixer that delivers just what you need, when you need it.

Standard Features

Model	L20R	
Control Console/Wireless System	Ranger control with integrated mix calculator and mix design storage Electric operated, manual controls	
Delivery Printer	No	
Two Way Remote	No	
Drive	Truck PTO	
Tarp Cover	Mesh manual open / close	
Unit Length	Depends on Chassis	
Unit Height	Depends on Chassis	
Unit Working Swing	N/A no swing	
Unit Weight (dry weight)	Under 25,950 lbs (11,770 kg) GVWR (with right chassis)	
Mixing Auger Diameter/Length	8" (203 mm) AR flight, 84", 2134mm repairable	
Chain Lubrication	Yes	
Water System	100 gallon (380L) standard	
Vibrators	Electric (Aggregate bins, cement bin, cement bag loader)	
Hydraulic Pumps	Rexroth	
Cement Bin capacity options	No	
Admix Tank 1 capacity	10.5 gallon (40L) (if optional admix selected)	
Admix Tank 2 capacity	10.5 gallon (40L) (if optional admix selected)	
Cement bag fill system	Standard	
Non-CDL operation (For US Market)	Non-CDL to operate (or local license for weight)	
Basic controls	Knobs to match target indicated	
Simple calibration	Supported for basic mix designs and up to three admixtures	
Skid steer loadable	Yes - 100" (2540 mm) rail side for loading	
Cement bag loading	Yes - silo not needed	
Operator training alignment	All screen pages follow same layout as PROALL RANGER series	
Chassis options	Ford F650, International MV-607, Freightliner M2-106 (ProAll supplied) or customer supplied (minimum 23,000 lbs / 10,433 kg)	
Voltage	12VDC and 24 VDC	
Powder coat paint	White (standard)	

